

SK135SR Offset Boom



■ Bucket capacity:

0.38 – 0.50 m³

■ Engine power:

73.0 kW/2,000 min⁻¹

■ Operating weight:

15,700 – 16,100 kg



SK 135SR



Performance Design

With the release of the SK135SR Offset Boom, KOBELCO has completely harmonised the values of PERFORMANCE and DESIGN. The SK135SR delivers greater efficiency and productivity with increased power and speed, along with uncompromising operator comfort and machine operability. In the pursuit of producing unique and unbeatable machines that provide comfort and productivity without equal, KOBELCO continues to rise to the challenge.

THE ULTIMATE SLEEK AND STYLISH CAB DESIGN

True ergonomic functionality combined with modern design has resulted in a cabin interior that is sleek and comfortable, built for simplicity and operator comfort.

Jog dial

The jog dial integrates multiple functions to allow for simple navigation of machine information screens, even while wearing gloves.

LED backlights

LED backlighting on switches and dials provides a bright, clear view of controls, even in the dark, while delivering a premium look and feel.







UNFORGETTABLE COMFORT

① Air suspension seat

A GRAMMER* seat is installed as standard equipment, which achieves excellent shock absorption and superior ride comfort.

*GRAMMER is trademark of GRAMMER AG. registered in Germany and other countries.



② Optimal air conditioning vent placement

Air conditioning vents are optimally placed around the cabin with air flow directed toward the operator's neck and back, providing more comfortable operation.

③ Ergonomic and low-effort pilot control levers

Pilot control levers are mounted on adjustable consoles, with an ergonomic design that allows movement without twisting, reducing operator fatigue.



New Hydraulic Control

Our newly upgraded hydraulic control system responds to shorter lever strokes than current models, delivering swifter, more precise movement and improved lever operability.



④ LED door light

The LED interior light automatically turns on when the door is opened or when the ignition is set to OFF. This ensures easy entry and exit at nighttime.

⑤ ROPS Cab

ROPS (Roll-Over-Protective Structure)-compliant cab clears ISO standards (ISO-12117-2: 2008) and ensures greater safety for the operator should the machine tip over.

KOBELCO



04:33



SETTING MENU



PICTURE OF
CAMERA



CLOCK
SETTING



SCREEN
BRIGHTNESS



MAINTENANCE




CONSUMPTION



LANGUAGE
SELECTION



PRESSURE
RELEASE




A WIDER VIEW BRINGS A WIDER RANGE OF USE

10-inch colour monitor—the largest in the industry

The easy-to-operate menu screen facilitates easy reading and navigation. Images from the built-in cameras can be checked on the large screen, which helps to improve safety. In addition, each icon is easily recognisable.



The right camera and rear camera (right side view mode)



The right camera and rear camera (straight view mode)



SAFETY ON FULL DISPLAY

Our high-resolution, large display shows right, left and rear side cameras together. Multiple camera modes allow operators to customize their display based on their needs to enhance awareness and jobsite safety.



Screen display linked with the jog dial operation

The jog dial provides simple and intuitive control of all display screens. Turn the jog dial to the right or left to select an item and press the dial to confirm the selection.

THE NEXT LEVEL OF PERFORMANCE

Our high-power engine complies with Tier 3 emissions regulations

Compared to previous models, engine output is significantly increased, which shortens cycle times substantially, while enabling greater breakout force for improved digging productivity.

The efficient engine complies with Tier 3 emissions standards, with no DPF and no additional requirement for AdBlue®.



Model: ISUZU 4JJ1XDJA

Engine output

73.0kW/2,000min⁻¹
(ISO14396 Without fan)

Performance

ADDED CAPABILITIES SMOOTH OUT ANY ROAD PROJECT



Standard equipment includes an offset boom, and a dozer blade makes swift work of excavation next to walls or of side ditches, as well as refilling.

585mm

Digging width at outer edge of right crawler

185mm

Digging width at outer edge of left crawler

Offset boom with hydraulic lines inside the cylinders to prevent damage

The press-constructed boom is both lightweight and slim for smooth operation. The large offset makes it easy to dig right next to walls.



Bucket Digging Force

92.9 kN (ISO6015)

Increased by 6%

(Compared to the SK135SR-2 offset model)



3,320mm

Min. working width

Compact working radius is ideal for road work in close quarters

The operator gets the best of both worlds: a roomy cab fitted on a compact upper body. With such a small working radius, the machine is perfect for continuous digging, swinging, and loading operations in tight spaces.

Smooth rotation cuts cycle times during swinging operation

Thanks to powerful swing torque and fast swing speed, digging, swinging, and loading — continuous operation makes any task faster.

GREATER MULTI-FUNCTION CAPABILITIES

Attachment mode

The flow-rate modes of the bucket, breaker, nibbler, and rotating grapple are set before delivery, which allows you to start operating immediately. Mode settings for other attachments, such as the tilt rotator, can easily be added or changed.





Adjustment for hydraulic flow

Divide ratio of hydraulic flow can be adjusted by service factory for custom usage.



NON-STOP OPERATION BY iNDr



iNDr Filter

A high-density stainless steel mesh filter blocks dust and debris from entering the cooling package during air intake. This prevents the cooling package and air cleaner from clogging, allowing the machine to maintain cooling performance. The ridges of the corrugated filter allow air to pass through, while the grooves collect dust and debris, preventing the filter from clogging.

CONVENIENT AND SENSIBLE EQUIPMENT



Adjustable height pilot control levers
Operator can adjust height of attachment control levers.



AM/FM Bluetooth® (hands-free) radio
Audio streaming and hands free phone calling capability.
*“Bluetooth®” is a registered trademark of the Bluetooth SIG Inc.



USB port / 12V power outlet



Smartphone holder
You can use the holder with your smartphone connected to the USB port.



Opening Top guard
The Top guard is hinged, allowing easy access to the top window for serviceability.



Standard built-in rear, left and right side cameras

GEOSCAN

GEOSCAN is the remote monitoring system for SK series excavators. When a hydraulic excavator is fitted with this system, data on the machine's operation, such as operating hours, location, fuel consumption, and maintenance status can be obtained remotely.



Specifications



Engine

Model	ISUZU 4JJ1XDJA
Type	Four-cycle, liquid-cooled, direct injection diesel, turbo charged, Tier 3 certified
No. of cylinders	4
Bore and stroke	95.4 mm x 104.9 mm
Displacement	2.999 L
Rated power output	65.4 kW/2,000 min ⁻¹ (ISO 9249: with fan) 73.0 kW/2,000 min ⁻¹ (ISO 14396: without fan)
Max. torque	341 N·m/1,600 min ⁻¹ (ISO 9249: with fan) 365 N·m/1,600 min ⁻¹ (ISO 14396: without fan)



Travel system

Travel motors	Variable displacement piston, two-speed motors
Travel brakes	Hydraulic brake
Parking brakes	Wet multiple plate
Travel shoes	44 each side
Travel speed	3.4 / 5.6 km/h
Drawbar pulling force	140 kN (SAE)
Gradeability	70% (35°)



Cab & control

Cab	All-weather, sound-suppressed steel cab mounted on the silicon-sealed viscous mounts and equipped with a heavy, insulated floor mat
Control	Two hand levers and two foot pedals for travel
	Two hand levers for excavating and swing
	Electric rotary-type engine throttle



Boom, arm & bucket

Boom cylinders	100 mm x 1,065 mm
Arm cylinder	115 mm x 965 mm
Bucket cylinder	95 mm x 885 mm
Offset cylinder	105 mm x 510 mm



Dozer blade (optional)

Dozer cylinder	125 mm x 220 mm
Dimension	2,490 mm (for 500 mm shoe) (width) x 570 mm (height)*
Working range	500 mm (up) x 590 mm (down)

*Dozer width is changed according to the shoe width difference.



Refilling capacities & lubrications

Fuel tank	186 L
Cooling system	17 L
Engine oil	17 L
Travel reduction gear	2 x 2.1 L
Swing reduction gear	1.65 L
Hydraulic oil tank	89.9 L tank oil level 186 L hydraulic system



Swing system

Swing motor	One fixed displacement piston motor
Brake	Hydraulic; locking automatically when the swing control lever is in the neutral position
Parking brake	Wet multiple plate
Swing speed	11.0 min ⁻¹
Swing torque	40.4 kN·m



Attachments

Backhoe bucket and combination

Use		Backhoe bucket		
		Normal digging		
Bucket capacity	ISO heaped struck	m ³	0.38 0.28	0.45 0.35
Opening width	With side cutter Without side cutter	mm	800 740	915 855
No. of teeth			4	4
Bucket weight		kg	340	360
Combination	2.20m standard arm 2.50m long arm		○ ◎	○ △ ×

○ Standard ○ Recommend ○ Loading only ○ Not recommended




Working ranges

Unit: m

Range	Arm	4.37 m					
		2.20 m			2.50 m		
		Max. Left	Center	Max. Right	Max. Left	Center	Max. Right
a-Max. digging reach		7.18	7.60	7.16	7.44	7.86	7.42
b-Max. digging reach at ground level		6.99	7.42	6.98	7.26	7.69	7.24
c-Max. digging depth		4.52	4.92	4.50	4.81	5.22	4.80
d-Max. digging height		7.75	8.09	7.74	7.91	8.25	7.90
e-Max. dumping clearance		5.43	5.77	5.42	5.59	5.93	5.58
f-Min. dumping clearance		2.11	2.44	2.10	1.82	2.15	1.81
g-Max. vertical wall digging depth		2.62	2.94	2.61	2.90	3.23	2.89
h-Min. swing radius		1.88	1.83	2.13	1.93	1.87	2.19
i-Horizontal digging stroke at ground level		3.78	3.76	3.78	4.25	4.22	4.25
j-Digging depth for 2.4 m (8') flat bottom		4.15	4.55	4.13	4.47	4.87	4.45
Bucket capacity ISO heaped m ³		0.45		0.38			

Illustration: 2.20 m arm



Digging force (ISO 6015)

Unit: kN

Arm length	2.20 m	2.50 m
Bucket digging force	92.9	
Arm crowding force	61.9	57.3



Dimensions

Unit: mm

Arm length	2.20 m	2.50 m
A Overall length	7,560	7,580
B Overall height (to top of boom)	2,690	2,740
C Overall width	2490*	
D Overall height (to top of cab)	2,860	
E Ground clearance of rear end**	870	
F Ground clearance**	400	

G	Tail swing radius	1,490
G'	Distance from centre of swing to rear end	1,490
H	Tumbler distance	2,870
I	Overall length of crawler	3,580
J	Track gauge	1,990
K	Shoe	500
L	Overall width of upperstructure	2,480
M	Dozer blade (up / down)***	500 / 590

*500 mm shoe **Without including height of shoe lug ***Dozer blade is optional equipment





Illustration: 2.20 m arm



Operating weight & ground pressure


In standard trim, with offset boom, 2.20 m arm, and 0.45 m³ ISO heaped bucket Dozer blade

Shaped		Triple grouser shoes (even height)		
Shoe width	mm	500	600	700
Overall width of crawler	mm	2,490	2,590	2,690
Ground pressure	kPa	49.2	41.8	36.3
Operating weight	kg	15,700	16,000	16,100

Lift capacities

SK135SR Offset Boom

SK135SR-7



- Rating over front
- Rating over side or 360 degrees

A - Reach from swing centerline to arm top
 B - Arm top height above/below ground
 C - Lift point
 Bucket: Without bucket
 Relief valve setting: 34.3 MPa (350 kgf/cm²)

SK135SR Offset boom		Arm: 2.20 m Bucket: Without Counterweight: 3,150 kg Shoe: 500 mm Dozer: Blade up								Radius		
A		1.5 m		3.0 m		4.5 m		6.0 m		At Max. Reach		Radius
B		Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	
6.0 m	kg							*2,650	*2,650			*2,620
4.5 m	kg							*4,060	*4,060			*2,510
3.0 m	kg							*6,010	*6,010			*2,640
1.5 m	kg							*8,080	5,220	4,480	3,310	2,060
G. L.	kg							*7,890	4,860	4,210	2,950	1,930
-1.5 m	kg	*6,220	*6,220	*7,790	4,860	4,140	2,720		2,750	1,820	2,600	1,750
-3.0 m	kg							*6,050	5,080			3,070
												*4,250
												2,980
												4.26 m
SK135SR Offset boom		Arm: 2.20 m Bucket: Without Counterweight: 3,150 kg + 580 kg Shoe: 500 mm Dozer: Blade up								Radius		
B		Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Radius
6.0 m	kg											*2,650
4.5 m	kg											*4,060
3.0 m	kg											*6,010
1.5 m	kg											*8,080
G. L.	kg											*7,890
-1.5 m	kg	*6,220	*6,220	*7,790	5,440	4,550	2,970					3,380
-3.0 m	kg											*6,050
												5,650
SK135SR Offset boom		Arm: 2.50 m Bucket: Without Counterweight: 3,150 kg + 580 kg Shoe: 500 mm Dozer: Blade up								Radius		
B		Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Radius
6.0 m	kg											*3,170
4.5 m	kg											*3,320
3.0 m	kg											*5,470
1.5 m	kg											*7,690
G. L.	kg											*8,060
-1.5 m	kg	*5,630	*5,630	*7,990	5,360	4,510	2,930					3,100
-3.0 m	kg	*8,960	*8,960	*6,520	5,530	4,320	3,020					*4,120
SK135SR Offset boom		Arm: 2.50 m Bucket: Without Counterweight: 3,150 kg + 1,000 kg Shoe: 500 mm Dozer: Blade up								Radius		
B		Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Rating	Radius
6.0 m	kg											*3,170
4.5 m	kg											*3,320
3.0 m	kg											*5,470
1.5 m	kg											*7,690
G. L.	kg											*8,060
-1.5 m	kg	*5,630	*5,630	*7,990	5,780	4,820	3,170					3,320
-3.0 m	kg	*8,960	*8,960	*6,520	5,950	4,320	3,250					*4,120

1. No attempt to lift or hold any load that is greater than these lift capacities at their specified lift point radius and heights. Weight of all accessories must be deducted from the above lift capacities.

2. Lift capacities are based on machine standing on level, firm, and uniform ground. User must make allowance for job conditions such as soft or uneven ground, out of level conditions, side loads, sudden stopping of loads, hazardous conditions, experience of personnel, etc.

3. Arm top is defined as lift point.

4. The above lift capacities are in compliance with ISO 10567. They do not exceed 87% of hydraulic lift capacity or 75% of tipping load. Lift capacities marked with an asterisk (*) are limited by hydraulic capacity rather than tipping load.

5. Operator should be fully acquainted with the Operator's and Maintenance Instructions before operating this machine. Rules for safe operation of equipment should be adhered to at all times.

6. Lift capacities apply to only machine as originally manufactured and normally equipped by KOBELCO CONSTRUCTION MACHINERY CO., LTD.

STANDARD EQUIPMENT

ENGINE

■ Engine, ISUZU MOTORS LIMITED 4J11XDJA, Direct injection type, with turbocharger, Tier 3 certified

■ Auto Idle Stop

■ Automatic engine deceleration

■ Batteries (2 x 12 V - 80 Ah)

■ Starting motor (24 V - 4.0 kW), 50 amp alternator

■ Engine oil pan drain cock

■ Double element air cleaner

CONTROL

■ Working mode selector (H-mode, S-mode and ECO-mode)

■ Auger & Breaker piping (proportional hand controlled)

■ Extra piping (proportional hand controlled)

■ Quick hitch piping

SWING SYSTEM & TRAVEL SYSTEM

■ Swing rebound prevention system

■ Straight propel system

■ Two-speed travel with automatic shift down

■ Sealed & lubricated track links

■ 500 mm steel shoes

■ Grease-type track adjusters

■ Automatic swing brake

MIRRORS, LIGHTS & CAMERAS

■ Left side rear view mirror,

■ Eagle-eye view camera (Rear, Right, Left)

■ LED work lights : 2 on boom, 1 on upper frame,

2 on rear counterweight

CAB & CONTROL

■ Two control levers, pilot-operated

■ Horn, electric

■ Integrated left-right slide-type control box

■ LED door light (interior)

■ Coat hook

■ Large cup holder

■ Detachable two-piece floor mat

■ GRAMMER® air suspension seat with heater

■ Retractable seatbelt

■ Headrest

■ Handrails

■ Intermittent windshield wiper with double-spray washer

Skylight

■ Opening top guard (ISO 10262: 1998)

■ Tinted safety glass

■ Pull-type front window and removable lower front window

■ Easy-to-read 10-inch LCD

■ SCREEN multi-display monitor

■ Automatic air conditioner

■ Emergency escape hammer

■ Radio (AUX & USB & Bluetooth®)

■ Hands-free telephone

■ 12 V converter

■ Travel alarm

■ GEOSCAN

■ Large footrest

■ Front roll screen

OPTIONAL EQUIPMENT

■ Various optional arms

■ Wide range of shoes

■ Wide range of buckets

■ Front-guard protective structure (may interfere with bucket action)

■ Additional counterweight (+580 kg)

■ Additional counterweight (+1,000 kg)

■ Cab top work LED lights (two lights)

■ Mechanical suspension seat

■ Rain visor

■ (may interfere with bucket action)

■ Additional track guide

■ Dozer Blade

(for 500mm, 600mm, 700mm shoe)

■ Multi control valve

Note: Standard and optional equipment may vary. Consult your KOBELCO dealer for specifics. Bluetooth® is a registered trademark of the Bluetooth SIG Inc. AdBlue® is a registered trademark of the Verband der Automobilindustrie e.V. (VDA). *GRAMMER is trademark of GRAMMER AG, registered in Germany and other countries.

Note: This catalogue may contain attachments and optional equipment that are not available in your area. And it may contain photographs of machines with specifications that differ from those of machines sold in your areas. Please consult your nearest KOBELCO distributor for those items you require. Due to our policy of continuous product improvements all designs and specifications are subject to change without advance notice.

Copyright by KOBELCO CONSTRUCTION MACHINERY CO., LTD. No part of this catalogue may be reproduced in any manner without notice.

KOBELCO CONSTRUCTION MACHINERY CO., LTD.

Tokyo, JAPAN

www.kobelcocm-global.com



Enquiries To: